

October 11, 2007

RECEIVED  
CENTRAL FAX CENTER

OCT 11 2007

**CLAIMS**

1  
2  
3 45. ( new) A wave and tide actuated submersible pump for use in an open body of water, said  
4 wave and tide actuated submersible pump comprising a pump cylinder (7) having an open  
5 top end and a closed bottom end (13), said cylinder (7) is affixed to a structure located in an  
6 open body of water, at least one [An] inlet check valve (11) and at least one [an] outlet  
7 check valve (12) connected to openings in the pump cylinder (7) near the lower end of said  
8 cylinder (7), said inlet check valve (11) allowing for the intake of water from the body of water  
9 and said outlet check valve (12) controlling the flow of water from the pump to a remote  
10 location, a ballast-weighted piston (8) vertically reciprocally movable within the pump cylinder  
11 (7) and forming a pump chamber defined by said cylinder walls, said ballast-weighted piston  
12 and bottom end of said cylinder, said piston ballast-weight is sufficient to pump the fluid in  
13 which it is contained while returning said piston to its' lowest point of travel, a buoy (1)  
14 connected to the ballast-weighted piston (8) by a flexible connector (4) for driving the ballast-  
15 weighted piston (8) on an upward stroke in response to wave action, said ballast-weighted  
16 piston (8) being driven in a downward stroke under force of gravity, a means for restricting the  
17 upward stroke of the ballast-weighted piston (8) within the pump cylinder (7), said flexible  
18 connector (4) passing through the top of said cylinder (7) and being attached to the top of the  
19 ballast-weighted piston (8) at a first end and to a lifting eye of the buoy (1) at a second end.  
20 46. (new) The wave actuated submersible pump of claim 45 wherein said means for  
21 restricting the upward stroke of the ballast-weighted piston is a plurality of stop pins (6) which

October 11, 2007

1 are securely attached and pass through openings adjacent said open top end of the pump  
2 cylinder (7).

3 47. (original) The wave actuated submersible pump of claim 45 wherein said lower plate (15)  
4 is a bottom plate end is suitable for imbedding the pump cylinder in the floor of the open body  
5 of water.

6 48. (original) The wave actuated submersible pump of claim 45 wherein said bottom  
7 enclosed end is a bottom flange plate (13) for securing the pump cylinder to submerged  
8 foundations at the floor of the open body of water.

9 49. (new) The wave actuated submersible pump of claim 45 wherein said ballast-weighted  
10 piston (8) includes sealing rings to provide a seal against the pump cylinder (7) .

11 50. (original) The wave actuated submersible pump of claim 45 wherein said buoy (1)  
12 includes a mooring eye (3) used to stabilize the direction of travel of the buoy (1).

13 51. (new) The wave actuated submersible pump of claim 45 wherein a mooring guide and  
14 wear ring (5) are mounted to the top open end of the pump cylinder (7), said connector (4)  
15 passing through the top of said cylinder said mooring guide and wear ring (5) [and being  
16 attached to the top of the ballast-weighted piston (8) at a first end and to a lifting eye (2) of the  
17 buoy (1) at a second end].

18 52. (new) The wave actuated submersible pump of claim 45 wherein said ballast-weighted  
19 piston (8) includes an air vent passageway (18), a check valve ball (19) and an air vent  
20 chamber (34) for allowing air entrapped within the pump chamber to vent through the air vent  
21 passageway and out the open top of the pump cylinder (7).

October 11, 2007

1 53. (original) The wave actuated submersible pump of claim 45 wherein the water pumped by  
2 the submersible pump is delivered by outlet check valve means (12) to a hydro-electric  
3 power plant (45).

4 54. (original) The wave actuated submersible pump of claim 45 wherein the water pumped by  
5 the submersible pump is delivered by outlet check valve means (12) to pump contaminated  
6 fluid into evaporation ponds or large bodies of water for mineral and chemical extraction,  
7 refinement (41) and toxic waste removal from contaminated fluids (39).

8 55. (original) The wave actuated submersible pump of claim 45 wherein the water pumped by  
9 the submersible pump is delivered by outlet check valve means (12) to pump salt water,  
10 creating large bodies of water and seas for the evaporation of said water thus forming  
11 moisture laden clouds where prevailing winds will blow these clouds to natural and man  
12 made barriers (50) causing rain to fall, creating new pasture and farmland (49) whilst  
13 moderating the earth's climate (51); said additional moisture will cleanse the atmosphere and  
14 the whole cycle shall act as a radiator cooling the earth.

15 56. (original) The wave actuated submersible pump of claim 45 wherein the water pumped by  
16 the submersible pump is delivered by outlet check valve means (12) to desalinate water (47)  
17 using pumps as a source of energy to extract fresh water from the saltwater.

18 57. (original) The wave actuated submersible pump of claim 45 wherein the water pumped by  
19 the submersible pump is delivered by outlet check valve means (12) to a levied reservoir to  
20 raise sea animals and organisms for the harvesting of said sea animals and organisms (43).

21 58. (original) The wave actuated submersible pump of claim 45 wherein the water pumped by  
22 the submersible pump is delivered outside a levied area by outlet check valve means (12) to

October 11, 2007

1 claim land from the sea by using these pumps with their suctions within the levied areas, to  
2 pump water out of said levied area (42).

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23